

Declaration of Performance

- | | |
|--|---|
| No.: | DoP Duct 001 |
| 1. Unique identification code of the product-type: | FEF Kaiflex Duct |
| 2. Intended use/es: | Thermal insulation for technical building equipment an industrial installations (ThIBEII) |
| 3. Manufacturer: | Kaimann GmbH
Hansastraße 2-5
D-33161 Hövelhof |
| 4. System/s of AVCP | 3 |
| 5. Harmonised standard: | Declaration of performance according to product standard EN 14304:2009+A1:2013 |
| Notified body/ies: | 0751 "Forschungsinstitut für Wärmeschutz e.V. München" |
| 6. Declared performance/s: | |

Essential Features		Performance				
Reaction to fire euroclass-characteristics	Reaction to fire	Sheet: d _N = 6 - 30 mm	E			
Acoustic absorption index	Structure-borne noise transmission Acoustic absorption		NPD			
Thermal resistance	Thermal conductivity Dimensions and limits	Sheet: d _N = 6 - 30 mm	°C	-10 °C	0 °C	10 °C
Water permeability	Water absorption		WS01 (W _p ≤ 0,1 kg/m ²)			
Water vapour permeability	Water vapour diffusion resistance	Sheet: d _N = 6 - 30 mm	MU 7.000 (μ ≥ 7.000)			
Release of corrosive substances	Minor amounts of water soluble chlorides and pH- value		500/7			
Release of dangerous substances to indoor environment	Release of dangerous substances		NPD ^a			
Continuous glowing combustion	Continuous glowing combustion		NPD			
Durability of reaction to fire against ageing/degradation	Durability characteristics ^b					
Durability of thermal resistance against ageing/degradation	Durability characteristics ^c					
	Maximum service temperature	Sheet: d _N = 6 - 30 mm	ST(+) 70 °C			
	Minimum service temperature	Sheet: d _N = 6 - 30 mm	ST(-) -40 °C			
Durability of reaction to fire Against high temperature	Durability characteristics ^b					
Durability of thermal resistance against high temperature	Durability characteristics ^c					

a No test method yet adopted.
b The fire performance of flexible elastomeric foam does not change with time.
c The thermal conductivity of flexible elastomeric foam does not change with time.
NPD = No Performance Determined
*λ₀ ≤ 0,036 + 7,1316 · 10⁻⁵ θ + 1,2533 · 10⁻⁶ θ²

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Andrea Trox, Head of Quality Management

A handwritten signature in black ink that reads "A. Trox".

Hövelhof, 21.11.2022