

Kaiflex Cleaner Technical Data

| Material | | Solvent-based cleaning agent | |
|--------------------------|-------|---|----------------|
| Application | | Removal of dust, dirt, grease and oil from surfaces prior to use Kaiflex adhesives. Removal of residues of Kailfex adhesives from surfaces, brushes etc | |
| Colour | | Colourless | |
| Appearence | | Clear liquid | |
| Flash point | | -4 °C | |
| Explosion limits | Lower | Approx. 0.6 Vol-% | |
| | Upper | Approx. 11.5 Vol-% | |
| Hazard classification | | VbF A1, highly flammable | |
| | | F1, Regulation of inflammable liquids | |
| Other safety information | | see Safety Data Sheet | |
| Waste treatment | | Disposal of waste according to applicable local and national regulations EWC No. 08 04 09 – waste adhesives and sealants containing organic solvents or other dangerous substances | See remark (1) |
| Transport information | | see Safety Data Sheet | |
| Storage / Shelf life | | 1 year | See remark (2) |
| Handling information | | see Safety Data Sheet | |

Remark (1) Classification of waste may change according to the field of application. Please observe Decision 2001/118/EC. Packaging must be emptied of all residues. Emptied packaging can be recycled. Packaging with traces of product must be disposed of in the same manner as the medium.

Remark (2) Shelf life is 1 year if stored in tightly closed containers. Store in upright position in a cool, dry and well ventilated place. See Safety Data Sheet for detailed information.

All values are based on results obtained under typical conditions of use. Recipient of these technical specifications are to check with Kaimann in advance if given values are meeting the specifications of intended area of application.

 $\ensuremath{\textcircled{O}}$ Kaimann GmbH | Subject to change without notice.

Page 1/1 · 09/2020

